

Lanopro Sliding-Oil 23-68 A



Slide/Circulation Oil

Product Data Sheet - 2010.12.06

Description

Lanopro Sliding-Oil 23-68 A is environmentally acceptable vegetable slide way oil.

Lanopro Sliding-Oil 23-68 A is recommended for use in metal processing machines where cutting oil is used.

The product is intended for machines with central lubrication systems.

Lanopro Sliding-Oil 23-68 A is designed to prevent stick slip on the slide ways.

Not recommended in machines using water miscible cutting fluids.

Physical and Chemical Data (typical)

Analysis	Method	Unit	Results
Viscosity at 40°C	ISO 3104	mm ² /s	65
Viscosity at 20°C	ISO 3104	mm ² /s	148
Density at 20°C	ISO 3675	kg/m ³	920
Colour	Optical		yellow / brown
Odour	Nasal		rapeseed related
Freezing Point	Own	°C	0
Flash Point	SS 150202	°C	228

Health and Safety Data

Analysis	Method	Unit	Results
Oral toxicity	OECD 401, LD ₅₀	mg/kg	> 2 000
Biodegradability	OECD 301B	-	readily biodegradable

Handling

• Storage

Handling and storage temperatures (0°C to +40°C)
Storage in closed container, preferably in the original package.

• Packaging

20L - 196L drums. Bulk and IBC tank on request.

ID No: D 100 121:2

Lanopro Production AS
Smedveien 7
1344 Haslum
Norway

Phone: +47 40 00 15 14
Fax: +47 21 54 73 43
E-mail: mail@lanopro.com
www.lanopro.com

Lanopro Pte Ltd
112 Robinson Road
#12-01
Singapore 068902

Phone: +65 6222 3209
Fax: +65 6826 4109
E-mail: mail@lanopro.com
www.lanopro.com