

# Lanopro Wire & Chain Spray 52-10 G

## Lubricant Spray



Product Data Sheet - 2010.12.06

### DESCRIPTION:

**Lanopro Wire & Chain Spray 52-10 G** is a light brown thin film aerosol spray coating with excellent penetration and corrosion resisting properties.

**Lanopro Wire & Chain Spray 52-10 G** is an oily coating product which is completely non-toxic and does not create an environmental footprint. It is a premium grade coating and lubrication formulated for frequent use in harsh conditions, whilst minimising lubricant build up and abrasive particle contamination. Designed for maximum lubrication and protection against degradation and corrosion. Suitable for wires and chains on i.e Tower Cranes, Mobile Cranes & Dockside Cranes. Also suitable for other open applications i.e chains, steel ropes, drilling tools, etc. where there is necessary with good lubrication, protection and penetration.

**Lanopro Wire & Chain Spray 52-10 G** is combatable with most mineral oils or other petroleum based products. Though, a test before application is recommended.

**Lanopro Wire & Chain Spray 52-10 G** is also available on 5L, 20L and 200 liter drums. The name of this product is **Lanopro 20-10 G**. It is recommended for long term protection and lubrication to conserve steel ropes with **Lanopro Wire Grease 50-70 G**.

### Physical and Chemical Data

Analysis	Method	Unit	Results
Form			Thin Liquid
Viscosity at 40°C	ASTM-D445		42.28 cSt
Density at 20° C	ASTM-D1298	kg/m <sup>3</sup>	921.1
Flash Point		°C	288
Colour			Light Brown
Copper Strip Corrosion	ASTM-D4048		1a
Odour			Faint or none

The product is non-toxic and has no negative environmental impact. It is approved for use in marine environments by Harmonized Offshore Chemical Notification Format (HOCNF). Use normal protective goggles to protect eyes. It is not necessary to take any special precautions for workers that use this product. See Material Safety Data Sheets (MSDS) for more information.

### Handling:

- **Storage** Storage temperatures (10°C to +40°C.)
- **Packaging** 12 Spray Cans per box

ID No: D 100 116:2

Lanopro Production AS  
Smedveien 7  
1344 Haslum  
Norway

Phone: +47 40 00 15 14  
Fax: +47 21 54 73 43  
E-mail: mail@lanopro.com  
www.lanopro.com

Lanopro Pte Ltd  
112 Robinson Road,  
#12-01  
Singapore 068902

Phone: +65 6222 3209  
Fax: +65 6826 4109  
E-mail: mail@lanopro.com  
www.lanopro.com