

Lanopro Wire Grease Classic 50-70 G

Grease



Product Data Sheet - 2010.07.08



WATER
RESISTANCE



CORROSION
PROTECTION



ENVIRONMENTALLY
FRIENDLY



LUBRICATION

DESCRIPTION:

Lanopro Wire Grease Classic 50-70 G is a light brown, firm lubrication and protection for steel ropes, which is completely non-toxic and does not create an environmental footprint. It is a premium grade coating designed for maximum protection against degradation and corrosion of the steel. The product forms a protective shield which protects against harsh conditions and corrosion. It also lubricates the steel ropes between the strings to avoid friction that can damage the steel rope. The grease will not crack or peel, and will prevent mildew while offering unbeatable weatherproof protection and excellent resistance under the most demanding conditions. If a semi dry film is needed, or easier application is **Lanopro Wire & Chain spray 52-10 G** recommended. As a wire oil it is recommended to use **Lanopro 20-10 G**.

Physical and Chemical Data:

Analysis	Method	Unit	Results
Form			Solid, dough-like
Viscosity at 40°C	ASTM-D445		76,18 cSt
Density at 20°C	ASTM-D1298	kg/m ³	927,8
Flash Point		°C	262
Colour			Ligth Brown
Copper Strip Corrosion	ASTM-D4048		1a
Odor			Without abnormal odor

The product is non-toxic and has no negative environmental impact. It is approved for use in marine environments by Harmonized Offshore Chemical Notification Format (HOCNF). Use normal protective goggles to protect eyes. It is not necessary to take any special precautions for workers that use this product. See Material Safety Data Sheets (MSDS) for more information.

Handling

- **Storage** Handling and storage temperatures (0°C to 40°C)
- **Packaging** 18kg Steel bucket.

ID No: D 100 138:1

Lanopro Production AS
Smedveien 7
1344 Haslum
Norway

Phone: +47 40 00 15 14
Fax: +47 21 54 73 43
E-mail: mail@lanopro.com
www.lanopro.com

Lanopro Pte Ltd
112 Robinson Road,
#12-01
Singapore 068902

Phone: +65 6222 3209
Fax: +65 6826 4109
E-mail: mail@lanopro.com
www.lanopro.com