

Lanopro Coating 10-15 G

Coating



Specification Sheet - 2010.12.06

DESCRIPTION

Lanopro Coating 10-15 G is a light brown thin coating with excellent penetration and corrosion resisting properties.

Lanopro Coating 10-15 G is an oily product which is completely non-toxic and does not create an environmental footprint. Designed for good lubrication, and semi protection against degradation and corrosion. The product forms a thin protective shield. Suitable for short time storage of equipment or tools. Also suitable for other open applications ie. chains, steel ropes, drilling tools, etc. where there is necessary with good lubrication, protection, and penetration.

Lanopro Coating 10-15 G is comparable in performance with most mineral oils or other petroleum based products. However, a test before application is recommended. A similar product to **Lanopro Coating 10-15 G** is available in aerosol cans for easy application. This product is **Lanopro Storage Spray 11-10 G**.

SURFACE PREPARATION

All surfaces must be free of dust, oil, gravel, or peeling paint and all other foreign matters. However, the product may be applied on rusty metal without any primer or brushing. Prior pressure washing of the surfaces is recommended for optimal results.

APPLICATION

It is recommended to stir before use. Apply with a soft bristle brush or broom, a long nap roller, or suitable spray equipment. Using an airless spray system is recommended (Lanopro can offer spray equipment on request). The coating can be used on both wet and dry surfaces. Under cold (<5°C) conditions it is beneficial to heat the product (25°C to 35°C is the ideal temperature) for better flow and spray ability. Coverage rates will vary depending on porosity of surface as well as speed of the application. Avoid apply unless temperature is 5°C or higher (refer to heating of the coating).

CLEAN UP

Clean brushes, tools and other equipment with soapy and/or hot water after use. Dried film may require warm water pressure cleaning. **Lanopro 84-01 Heavy Cleaner and remover** is also recommended as it is an environmental friendly degreaser.

PHYSICAL PROPERTIES

The product is non-toxic and has no negative environmental impact. It is approved for use in marine environments by Harmonized Offshore Chemical Notification Format (HOCNF). Use normal protective goggles to protect eyes. It is not necessary to take any special precautions for workers that use this product. See Material Safety Data Sheets (MSDS) for more information.

Copyright © 2009 – Lanopro Pte Ltd

ID No - S 100 110:2

Lanopro Production AS
Smedveien 7
1344 Haslum
Norway

Phone: +47 40 00 15 14
Fax: +47 21 54 73 43
E-mail: mail@lanopro.com
www.lanopro.com

Lanopro Pte Ltd
112 Robinson Road
#12-01
Singapore 068902

Phone: +65 6222 3209
Fax: +65 6826 4109
E-mail: mail@lanopro.com
www.lanopro.com