

LanoPro Super CSX Grease HD2

Heavy Duty Marine Multi-Purpose Grease



Product Data Sheet - 2017.03.01



EXTREME
PRESSURE



HEAVY
LOADS



CORROSION
PROTECTION



WATER
RESISTANCE



HIGH
TEMPERATURE

Description

LanoPro Super CSX Grease HD2 is a calcium sulfonate complex thickened lubricating grease based on mineral oil. The grease contains antioxidants and corrosion inhibitors.

The functional thickener with built-in EP and AW properties gives the product extreme load carrying capacity making it suitable for heavily loaded applications. The grease also has superb mechanical stability, good corrosion protection and excellent water resistance.

LanoPro Super CSX Grease HD2 is a modern high performance lubricant suitable for applications in industrial, marine and rough environments. The strong properties make the product a perfect choice for heavily loaded applications in hot or wet and corrosive environments.

- Extreme load carrying capacity
- Very good mechanical stability
- Good corrosion protection
- Excellent water resistance

Technical Data

Properties	Test Method	Typical Values
Thickener		Calcium sulfonate complex
Base fluid		Mineral oil
Colour	Visual	Brown
NLGI grade	ASTM D 217	2
Dropping point	IP 396	>280°C
Base oil viscosity at 40°C	ASTM D 7152	290 mm ² /s
Penetration 60 strokes	ISO 2137	265-295
4-ball weld load	DIN 51350:4	6500 N
Water resistance at 90°C	DIN 51807:1	1
Temperature range		-30°C to +140°C (max +180°C)

Handling

- **Storage** Handling and storage temperatures (0°C to 40°C)
- **Packaging** 18kg - 180kg. Other on request

ID No: D 100 187:1

LanoPro Production AS
Smedveien 7
1344 Haslum
Norway

Phone: +47 40 00 15 14
Fax: +47 21 54 73 43
E-mail: mail@lanopro.com
www.lanopro.com

LanoPro Pte Ltd
112 Robinson Road,
#12-01
Singapore 068902

Phone: +65 6222 3209
Fax: +65 6826 4109
E-mail: mail@lanopro.com
www.lanopro.com