

LanoPro Multi Grease EP2



Multi-Purpose EP Grease - NLGI 2

Product Data Sheet - 2016.10.01

Previous product name: LanoPro EP Grease 154-2



MULTI
PURPOSE



EXTREME
PRESSURE



CORROSION
PROTECTION

Description

LanoPro Multi Grease EP2 is a lithium thickened lubricating grease based on mineral oil. The grease contains antioxidants, corrosion inhibitors and EP/AW additives.

The product is a state-of-the-art multi-purpose EP grease which can be used in various applications within given temperature limits. The lubricating grease offers good mechanical stability, load carrying capacity and corrosion protection, which makes it suitable for loaded bearings as well as wet environments.

LanoPro Multi Grease EP2 is a high quality multi-purpose grease that can be used in marine, industrial and automotive applications.

- Good mechanical stability
- High load carrying capacity
- Good corrosion protection

Technical Data

Properties	Test Method	Typical Values
Thickener		Lithium
Base fluid		Mineral oil
Colour	Visual	Yellowish-brown
NLGI grade	ASTM D217	2
Dropping point	IP 396	>180°C
Base oil viscosity at 40°C	ISO 12058	200 mm ² /s
Penetration 60 strokes	ISO 2137	265-295
4-ball weld load	DIN 51350:4	2600 N
Water resistance at 90°C	DIN 51807:1	0-90
Temperature range		-30°C to +120°C Max +130°C

- **Storage** Handling and storage temperatures (0°C to 40°C)
- **Packaging** 18kg - 180kg. Other on request

ID No: D 100 160:1

LanoPro Production AS
Smedveien 7
1344 Haslum
Norway

Phone: +47 40 00 15 14
Fax: +47 21 54 73 43
E-mail: mail@lanopro.com
www.lanopro.com

LanoPro Pte Ltd
112 Robinson Road,
#12-01
Singapore 068902

Phone: +65 6222 3209
Fax: +65 6826 4109
E-mail: mail@lanopro.com
www.lanopro.com