

LanoPro Multi Grease WRM2



Multi-Purpose Grease EP2 - NLGI 2

Product Data Sheet - 2022.08.04



MULTI
PURPOSE



EXTREME
PRESSURE



CORROSION
PROTECTION



WATER
RESISTANCE

Description

LanoPro Multi Grease WRM2 is a calcium thickened lubricating grease based on mineral oil. The grease contains antioxidants, corrosion inhibitors and EP/AW additives. The thickener, together with the special base oil blend, makes the product suitable for various applications and in wet / corrosive environments. The lubricating grease has excellent adhesion and water resistance.

LanoPro Multi Grease WRM2 is a high quality multipurpose grease that can be used in marine, mining, industrial and automotive applications within given temperature limits. The grease is suitable for a wide range of plain and rolling bearings. The properties of the grease makes it highly recommended as a maintenance grease for wire ropes. The product is also suitable for application during the manufacturing process of steel wire ropes and forms a protective & lubricating shield in between the wire strings and steel rope

- Very good water resistance
- Good corrosion protection
- Wide range of uses
- Good mechanical stability
- Good load carrying capacity

Technical Data

Properties	Test Method	Typical Values
Thickener		Calcium
Base fluid		Polymer mineral oil
Colour	Visual	Yellow
NLGI grade	ASTM D217	2
Dropping point	IP 396	>140°C
Base oil viscosity at 40°C	ASTM D 7152	250 mm ² s
Penetration 60 strokes	ISO 2137	265-295
4-ball weld load	DIN 51350:4	2600 N
Water resistance at 90°C	DIN 51807:1	0
Temperature range		-30°C to +120°C

Handling

- **Storage** Handling and storage temperatures (0°C to 40°C)
- **Packaging** 18kg - 180kg. Other on request

ID No: D 100 188.5

LanoPro Production AS
Smedveien 7
1344 Haslum
Norway

Phone: +47 40 00 15 14
Fax: +47 21 54 73 43
E-mail: mail@lanopro.com
www.lanopro.com

LanoPro Pte Ltd
112 Robinson Road,
#12-01
Singapore 068902

Phone: +65 6222 3209
Fax: +65 6826 4109
E-mail: mail@lanopro.com
www.lanopro.com