

LanoPro FG Grease ST2

Food Grade Grease



Product Data Sheet - 2022.08.16



EXTREME
PRESSURE



HEAVY
LOADS



FOOD
MACHINERY

Description

LanoPro FG Grease ST2 is an aluminium complex thickened lubricating grease based on pharmaceutical white oils. The grease contains antioxidants and EP/AW additives. The thickener, together with the special base oil, makes the product suitable for lubrication in applications where there is the possibility of incidental or accidental food contact.

LanoPro FG Grease ST2 is a high performance universal food machinery grease. The product's all round properties make it suitable for various types of bearing applications including heavy load conditions. NSF, Kosher, Halal and Allergen approved.

- Good oxidation stability
- Excellent load carrying capacity
- Suitable for food machinery

Technical Data

Properties	Test Method	Typical Values
Thickener		Aluminium complex
Base fluid		Pharmaceutical white oil
Colour	Visual	White
NLGI grade	ASTM D217	2
Dropping point	IP 396	> 230 °C
Base oil viscosity at 40°C	ISO 12058	550 mm ² /s
Penetration 60 strokes	ISO 2137	265-295
4-ball weld load	DIN 51350:4	6000 N
Water resistance at 90°C	DIN 51807:1	1-90
Temperature range		-20°C to +120°C Max +140°C



Nonfood Compounds
Program Listed H1
Registration N° 145257



HALAL CERTIFIED



KOSHER CERTIFIED

Handling

- Storage Handling and storage temperatures (0°C to 40°C)
- Packaging 400gr - 18kg - 180kg. Other on request

ID No: D 100 162:2

LanoPro Production AS
Smedveien 7
1344 Haslum
Norway

Phone: +47 40 00 15 14
Fax: +47 21 54 73 43
E-mail: mail@lanopro.com
www.lanopro.com

LanoPro Pte Ltd
112 Robinson Road
#12-01
Singapore 068902

Phone: +65 6222 3209
Fax: +65 6826 4109
E-mail: mail@lanopro.com
www.lanopro.com