

LanoPro Green Shield

H39




Product Data Sheet: 24.05.15

Description

A highly refined lanolin product with lanolin's unique properties, but without any annoying smell. Lanolin oil is a renewable natural product. The coating is hypoallergenic and gentle on natural rubber, synthetic rubber and sensitive types of plastic. The product has very good anti-rust properties, lubrication properties and wear resistance. The product has a large area of application, such as: Underbody treatment of cars, tractors, trucks and motorhomes. Can also be used on boats. Can be used as a lubricant on moving parts. The product does not drip and has a pleasant scent. Necessary information is available at www.lanopro.no/en



CORROSION
PROTECTION



LUBRICATION



ENVIRONMENTALLY
ACCEPTABLE

- Stops rust
- Prevents rust
- Long-term protection
- Does not crack or peel
- Displaces moisture

Technical Data

Properties	Test Method	Typical Values
Consistency		Semi liquid
Colour	Visual	Light yellow
Odour		None or faint apple
Flash point	ASTM-D92	>200°C
Viscosity at 40°C	ASTM-D445	130 mm ² /s
Copper strip corrosion	ASTM-D4048	1a
Density at 20°C	ASTM-D1298	0.94
Temperature range		0°C to +80°C



Surface Preparation

All surfaces must be free of dust, oil, gravel, or peeling paint and all other foreign matters. However, the product may be applied on rusty metal without any primer or brushing. Prior pressure washing of the surfaces is recommended for optimal results.

Application

The product can be applied by brush, roller or spray. The product can also be sprayed. It should then be heated to approximately 40°C for easier application.

Document ID - D 100 235.1

LanoPro Production AS
Smedveien 7
1344 Haslum
Norway

Phone: +47 40 00 15 14
E-mail: mail@lanopro.com
www.lanopro.com

LanoPro Pte Ltd
105 Cecil Street, #18-18,
The Octagon,
Singapore 069534

Phone: +47 40 00 15 14
E-mail: mail@lanopro.com
www.lanopro.com