

LanoPro Green Shield

H44 BIO



Produkt datablad: 25.06.23

Description

This is a thin, specialized product approved with the EU Ecolabel. It is developed to protect against rust and to lubricate areas that are difficult to reach, making it especially suitable for doors and cavities in cars, motorhomes, trucks, and tractors. The product is easy to spray on, does not drip, and is gentle on both rubber and plastic. It is also well-suited for use on boats and other areas where good, but not extreme, protection is needed. For areas exposed to extra wear or harsh weather, we recommend a stronger and thicker product, such as Green Shield SH36. Read more at www.lanopro.no/en

Technical Information

Properties	Test Method	Typical Values
Consistency		Thin liquid
Colour	Visual	Light yellow
Odour		None or faint
Flash point	ASTM-D92	>200°C
Viscosity at 40°C	ASTM-D445	110 ² / ₅
Copper strip corrosion	ASTM-D4048	1a
Temperature range		0°C to + 80°C

Surface Preparation


All surfaces must be free from dust, oil, gravel, flaking paint, and any other foreign substances. However, the product can be applied to rusty metal without the use of primer or brushing. For extremely dirty areas, it is recommended to pre-wash the surfaces with a pressure washer for optimal results.

Application

The product can be applied with a brush, roller, or spray. It can also be sprayed. The temperature should be at least room temperature for easier application.



CORROSION
PROTECTION



LUBRICATION



ENVIRONMENTALLY
ACCEPTABLE

- Stops rust
- Prevents rust
- Long-lasting Effect
- Displaces Moisture
- Excellent penetration
- Excellent Lubrication Properties



Document ID - D 100 272.1

LanoPro Production AS
Smedveien 7
1344 Haslum
Norway

Phone: +47 40 00 15 14
E-mail: mail@lanopro.com
www.lanopro.com

LanoPro Pte Ltd
105 Cecil Street, #18-18,
The Octagon,
Singapore 069534

Phone: +47 40 00 15 14
E-mail: mail@lanopro.com
www.lanopro.com